

Money exchange rate screen



1:1



Money exchange rate screen Operation manual

1. Within a certain range (3 Meters) of the remote control flashes front of the second point of the display board position (if the remote control does not work, check the battery is valid or stand far)
2. Figures modification method of exchange rates sign:

1) The position of the remote control  at the screen time flashing press the green button, that the first one digital flash , then you can adjust the digital information.

2) Enter numbers "0-9" decimal point "EQ" modify the figures until the right to delete a number, press "BAND".

A: Press the arrow keys to enter the next which data values or data values .

B: Adjustment is completed,  press the red button to determine the led display and can save and exit automatically and display normally.

3. Press the green button,  the remote control at the screen time flashing position appears to exchange one digit is flashing, press "CLK", the exchange rate stops flashing, press the right arrow

 to move , modify year , month, date , day of the week ,when , sub . Adjustment is completed,

 Press the red button to determine the led display and can save and exit automatically and display normally.





Specifications:

- A. Backup memory, keep the latest exchange rates when the power off.
- B. Date and time display, with built-in RTC (real time clock).
- C. Six digits, 1 Inch high definition per field.
- D. Each column included flag and country name in additional to BUY and SELL fields.
- E. Flags of countries fixing by magnetic strip.
- F. Rates, Date/Time and bright message can be managed by PC via RS232, TCP/IP.
- G. Rates, Date/Time and bright message can be changed by remote control.
- H. Ability to update the rates automatic by internet, Ability to update the rates automatic by internet.
- I. Ability to show Precious Metals prices, "Optional".
- J. Currencies rows expandable to 24 rows.
- K. Power: 90-250VAC power supply built in.